

LOGIBALL SECURIMAX PLUGS



The SECURIMAX plugs are the improved version of the well known Logiball Plugs. Safety factors have been improved, anchoring devices have been redesigned and end plate retaining devices have been added.

Every plug must pass a severe pressure test, is identified with a serial number, and supplied with a test certificate and a leaflet describing the features of the plug and information on its safe use.

Pipe Size (inches)	Inflation Pressure ¹	Diameter (inches)	Weight (lbs)	Length (inches)	Models Available
4-8	45 psi	3.5	6	17	B
5-10	45 psi	5.0	15	21.5	A, B, C
7-12	35 psi	6.6	26	28.5	A, B, C
9-16	35 psi	8.6	37	30	A, B, C
11-21	35 psi	10.75	50	35.5	A, B, C
13-24	35 psi	12.75	66	39	A, B, C
17-30	25 psi	16.6	160	58	A, B, C
19-36	20 psi	18.75	195	64	A, B, C

Model A: No-flow-thru

Model B: 1/2" flow-thru on the 4-8
2" flow-thru on the 5-10 & up

Model C: Two 1/2" flow-thru hoses

Color coded safety inflation systems with or without poly lift rope are available.



¹ At these pressures, the plugs will make a tight seal and safely withstand a back pressure of 5 p.s.i. or 12 feet of water in structurally sound and clean pipes.

www.logiball.com

Tel.: 418-656-9767

800-246-5988