

LOGIPLUGS

MULTISIZE LARGE FLOW-THRU INFLATABLE PLUGS



The Logiplugs are used in a large variety of applications such as bypass pumping & flow diversion. They can also be used for stopping the flow when the flow thru is plugged off.

The Logiplugs are manufactured on lightweight aluminum mandrels. Steel & stainless steel mandrels are also available. The SBR rubber sleeve is reinforced with two plies of nylon cords. Different elastomers are available for different environments. All plugs must pass a severe pressure test and are shipped with their individual inspection reports and safety information pamphlets.

Custom configurations always possible. Factory replaceable rubber sleeves.

Logiplug Product #	Pipe Size (inches)	Flow-thru Size (FPT)	Inflation Pressure ¹	O.D.	Length	Weight
4-8LP	4 to 8	2" MPT	45 PSI	3.75"	22"	7.5 lbs
6-10LP	6 to 10	2" FPT	35 PSI	5.5"	18.5"	14 lbs
7-12LP	7 to 12	3" FPT	35 PSI	6.5"	18.5"	16 lbs
7-12LPM	7 to 12	4" MPT	35 PSI	6"	22.5"	18 lbs
9-16LP	9 to 16	4" FPT	30 PSI	8"	18.5"	20 lbs
12-18LP	12 to 18	4" FPT or 6" MPT	30 PSI	10"	28"	33 lbs
15-21LP	15 to 21	6" FPT	25 PSI	14"	24"	57 lbs
18-24LP	18 to 24	6" or 8" FPT	25 PSI	16.5"	28"	75 lbs

¹ At these pressures, the plugs will make a tight seal and safely withstand a back pressure of 5 p.s.i. or 12 feet of water in structurally sound and clean pipes.



Optional remote placement pole assembly available in 6 foot long pole segments.



Logiplug 7-12M with 4" MPT by-pass



Color coded safety inflation systems with or without poly lift ropes are available.

www.logiball.com

Tel.: 418-656-9767

800-246-5988